

ExperTherm SR 12

COLOR OPTIONS: Grey

15

±%2 KG



Heat and Sound Insulation Materials

998-1 103115

GÜVEN MADENCİLİK İNŞAAT SAN. ve TİC. A.Ş.

CEMENT BASED, POLYMER AND PUMICE ADDED INSULATION RENDER WITH INCREASED SOUND PROOFING FEATURE

Cement based, polymer and pumice added, single component, insulation render with 50% increased sound proofing feature and at the same time thermal and fire insulation features.



SOUND
PROOFING



SUITABLE
FOR MACHINE
APPLICATION

TECHNICAL SPECIFICATIONS

Chemical Structure	Cement based, polymer and pumice added powder
Dry Unit Weight	~400 kg/m ³ (±200)
Wet Unit Weight	~850 kg/m ³ (±200)
Water Mixture Ratio	14,00-15,00 lt water / 15 kg powder
Thermal Conductivity	T1 ≤ 0,1 W/m.K
Compressive Strength	CS I ≥ 1 N/mm ² (EN 1015-11)
Bond Strength	≥ 0,1 N/mm ² (EN 1015-12)
Capillary Water Absorption	W1; C ≤ 0,40 kg/(m ² .minute 0,5) (EN 1015-18)
Water Vapor Permeability	≤ 15
Reaction to Fire	A1
Sound Retention	17dB (TS 2382-TS 1477-TS EN 20140-10)
Pot Life	Maximum 2 hours
Full Curing Time	28 days
Consumption	4,50 kg/m ² (for 10 mm application thickness)

* All technical values are calculated at +23°C and 50% relative humidity. Changes in temperature and humidity change the technical values.

ADVANTAGES

- Easy and fast to apply.
- Suitable for machine application.
- Saves labor and time.
- Forms a solid layer with high bond and durability strengths.
- Shows high resistance against crack formation.
- It has high sound proofing feature.
- Provides heat, sound and fire insulation with a single product.
- Contributes to the budget in heating and cooling costs.
- Prevents condensation (bleeding), mold and moisture.
- High water vapor permeability.
- Lightweight, reduces the load of the structure.

APPLICATION AREAS

Especially used for sound insulation purposes:

- Interior facades,
- In insulation applications of all mineral based surfaces such as pumice block, gas concrete, brick, briquette wall, exposed concrete etc.

ExperTherm SR 12

COLOR OPTIONS: Grey

15

±%2 KG



Heat and Sound
Insulation Materials

**998-1
103115**

GÜVEN MADENCİLİK İNŞAAT SAN. ve TİC. A.Ş.

SURFACE AND APPLICATION CONDITIONS

- Ambient temperature should be between +5°C and +35°C.
- Avoid application in strong wind or sun.
- Do not apply on surfaces that are frozen, melting or in danger of rain or frost within 24 hours.

SURFACE PREPARATION

- The application surface must be clean, smooth and solid. Dust, dirt, paint, oil and free particles must be removed from the surface.
- If there are any damages on the surface that may affect the application, they should be repaired with ExperRepair repair mortar 24 hours before the application.
- The surface must be moisturized before application; it must be saturated with water in very hot and windy weather.
- Wood-based lightweight boards, thermal insulation boards and exposed surfaces should be primed with ExperPrime CP 50 or ExperPrime AP 31 exposed concrete primer and made ready for application.
- If primer is applied to the surface before ExperTherm SR 12 application, wait 24-72 hours depending on weather conditions for plaster application.

PREPARATION OF MIXTURE

- Add 14,00-15,00 lt of clean water to 15 kg ExperTherm SR 12 poured into a clean bowl. Mix with a low speed mixer until a homogeneous and lump free mixture is obtained.
- The mixture is allowed to rest for approximately 10 minutes, then mixed again for 2-3 minutes and made ready for application.

APPLICATION DETAILS

- Once the mixture is completed, apply the material to the surface with a steel trowel or machine and then smooth it with a cartridge.
- Make sure that the plaster is applied evenly and spread over the entire surface.
- The first coat application thickness should be between 15-20 mm.
- After the first coat has set, apply the second coat in the same way.
- Total application thickness should be 30-50 mm.
- The waiting time between coats is approximately 24 hours depending on weather conditions.
- The surface must be ruled to obtain a smooth surface.
- The surface should be moisturized for 2-3 days after application.

WARNINGS

- Do not apply in weather conditions below +5°C, above +30°C, in rainy and/or windy weather.
- Avoid application in areas that are frozen, in areas with the risk of freezing within 24 hours, in conditions that may prevent the application or that may damage the surface after application.
- Wait 2-3 days, depending on weather conditions, for the topcoat to be applied.
- No foreign materials such as lime, cement, gypsum etc. should be added to the prepared mortar.

CONSUMPTION

- 4,50 kg/m² (For 10 mm application thickness)

EQUIPMENT CLEANING

- Equipment should be cleaned with solvent immediately after use. Cured material can only be cleaned by mechanical means.

STORAGE AND SHELF LIFE

- Should be stored in its unopened original packaging, in a closed, moisture-free, dry environment, protected from frost. Products should not be overloaded in a way to damage their packaging.
- Shelf life under appropriate storage conditions is 12 months from the date of production.

ExperTherm SR 12

COLOR OPTIONS: Grey

15

±%2 KG



Heat and Sound
Insulation Materials

**998-1
103115**

GÜVEN MADENCİLİK İNŞAAT SAN. VE TİC. A.Ş.

SAFETY PRECAUTIONS

- During use and storage, work clothes, protective gloves and masks should be used in accordance with the rules of Occupational and Labor Health. Eye, mouth and skin contact should be avoided and the contact area should be washed with plenty of water.
- In more dangerous situations or in case of ingestion of the product, a specialist doctor should be consulted immediately. Food and beverages should not be brought into the application areas. Keep out of the reach of children. For detailed information, the Safety Data Sheet (SDS) should be consulted.

PRODUCT LIABILITY

- Güven Madencilik İnş. San. ve Tic. A.Ş., is only responsible for the quality of EXPERAS branded products. All data presented are the result of practical and scientific studies. The manufacturer cannot be held responsible except for the use of the correct products in appropriate areas and conditions.

LEGAL NOTES

- The information and recommendations for the use of EXPERAS branded products are provided in good faith based on technical knowledge and experience, provided that they are maintained and handled under normal conditions and in accordance with the recommendations. Along with the products, the areas of use and surfaces may vary widely. It is necessary to ensure that the correct EXPERAS branded products are applied on appropriate surfaces and under appropriate conditions. In addition, all information and instructions regarding commercial factors and technical conformity must be strictly followed. The manufacturer cannot be held responsible for any damages and problems that may occur if not complied with. The applicator/user is obliged to make the relevant checks to ensure these details. The specifications of EXPERAS branded products may be changed when necessary. The property rights of third parties must be respected. When the order is confirmed, all existing technical conditions are essential for sales and transportation.

REFERENCE STANDARDS

- TS EN 998-1

